

a first power supply unit including a first inverter for outputting a DC voltage and no filter, and


*Correct*  
a second power supply unit including a second converter for outputting a DC voltage connected to the first inverter in series, and a DC filter connected to output ports of the second inverter in parallel, and wherein

the scanning electromagnet is connected to the first inverter and the second inverter in series.

REMARKS

Examination is requested.

Respectfully submitted,

  
John R. Mattingly  
Registration No. 30,293  
Attorney for Applicant(s)

MATTINGLY, STANGER & MALUR, P.C.  
1800 Diagonal Road, Suite 370  
Alexandria, Virginia 22314  
(703) 684-1120  
Date: November 5, 2002

**MARKED UP VERSION OF REWRITTEN CLAIMS**

4. (Once Amended) A charged particle beam irradiation equipment, for applying a charged particle beam to an irradiation area, comprising a scanning electromagnet for deflecting the charged particle beam and a power supply for applying a voltage to the scanning electromagnet, characterized in that

the power supply comprises;

a first power supply unit including a first inverter  
for outputting a DC voltage and no filter, and

a second power supply unit including a second  
converter for outputting a DC voltage connected to the first inverter in series, and a DC filter connected to output ports of the second inverter in parallel, and wherein

the scanning electromagnet is connected to the first inverter and the second inverter in series.